Commonwealth of Kentucky Division for Air Quality

PERMIT APPLICATION SUMMARY FORM

Completed by: D. Brian Ballard

GENERAL INFORMATION:	
Name: Toyota Motor Manuf	acturing Kentucky, Incorporated
Address: 1001 Cherry Blosso	om Way, Georgetown, KY 40324
Date application received: Fe	ebruary 16, 2004
SIC/Source description: 3711	1/Automobile Assembly
EIS #: 21-209-00030	
Application log number: 563-	40
Permit number: V-04-027	
APPLICATION TYPE/PERMIT ACTIVITY	• •
[] Initial issuance	[] General permit
[] Permit modification	[]Conditional major
Administrative	[X] Title V
Minor	[] Synthetic minor
Significant	[] Operating
[] Permit renewal	[X] Construction/operating
COMPLIANCE SUMMARY:	
[] Source is out of complian	nce [] Compliance schedule included
[X] Compliance certification	signed
APPLICABLE REQUIREMENTS LIST: [] NSR [X] PSD	[X] NSPS [] SIP [] NESHAPS [] Other
[] Netted out of PSD/NSR	
MISCELLANEOUS: [] Acid rain source	
[] Source subject to 112(r)	
[] Source applied for federal	lly enforceable emissions cap
	or alternative operating scenarios
[X] Source subject to a MAC	· •
	y-case 112(g) or (j) determination
[] Application proposes nev	· · · · · · · · · · · · · · · · · · ·
[X] Certified by responsible of	
[X] Diagrams or drawings in	
0	formation (CBI) submitted in application
[] Pollution Prevention Mea	
[] Area is non-attainment (li	
E 3	1 /

EMISSIONS SUMMARY:

	VOC (tpy)		PM/PM ₁₀ (tpy)	
Department	Current Allowable	New Potential	Current Allowable	New Potential
Assembly	614.10	130.80	13.26	5.26
Body Operations	276.60	262.00	40.61	25.73
Paint	3695.50	1861.60	81.01	59.05
Plastics	1828.50	1024.60	73.29	67.11
Powertrain	182.40	182.40	16.10	16.10

TABLE 1-VOC and PM/PM $_{10}$ Current Allowable and New Potential Emissions for Assembly, Body Operations, Paint, Plastics and Powertrain shops.

HAPS	CAS#	Actual (tpy)	Potential (tpy)
Ethyl benzene	100-41-4	193	289
Styrene	100-42-5	7.0	10.5
Methylene diphenyl			
diisocyanate (MDI)	101-68-8	0.2539	0.3804
p-Xylenes	106-42-3	0.0895	0.1342
Ethylene glycol	107-21-1	64	95
Methyl isobutyl			
ketone (Hexone)	108-10-1	63	94
Toluene	108-88-3	354	531
Chlorobenzene	108-90-7	0.6064	0.9087
Hexane	110-54-3	2.77	4.15
Bis(2-			
ethylhexyl)phthalate			
(DEHP)	117-81-7	2.20	3.29
Triethylamine	121-44-8	15.53	23.27
1,4-Dioxane (1,4-			
Diethyleneoxide)	123-91-1	0.0105	0.0158
Xylenes (isomers			
and mixture)	1330-20-7	1134	1700
Formaldehyde	50-00-0	35.19	52.73
Carbon tetrachloride	56-23-5	0.0041	0.0061
Methanol	67-56-1	179	268
Benzene (including			
benzene from	-		
gasoline)	71-43-2	0.1917	0.2873
Methyl chloroform			
(1,1,1-	74.55.0	0.7040	4 4004
Trichloroethane)	71-55-6	0.7343	1.1004
Vinyl chloride	75-01-4	0.0125	0.0188
Propylene oxide	75-56-9	0.0010	0.0015
Methyl ethyl ketone	70.00.0	00	4.40
(2-Butanone)	78-93-3	98	146
Acrylic acid	79-10-7	0.00012	0.00017
Methyl methacrylate	80-62-6	0.0069	0.0103
Phthalic anhydride	85-44-9	5.59	8.37
Naphthalene	91-20-3	88	131
Cumene	98-82-8	18.41	27.58

TABLE 2 – Actual and Potential Source Wide HAP Emissions for Calendar Year 2003.

EMISSIONS SUMMARY (CONTINUED):

Facilities Control	(tpy)	
	Current Allowable	Potential
PM/PM ₁₀	57.81	57.81
SO ₂	9.33	9.33
NO _X	651.23	651.23
СО	533.80	533.80
VOC	29.40	29.40

TABLE 3 – Products of Combustion Current Allowable and Potential Emissions from Facilities Control.

SOURCE PROCESS DESCRIPTION: See Statement Of Basis

EMISSION AND OPERATING CAPS DESCRIPTION:

BACT Limits per Shop	VOC (tpy)	PM/PM ₁₀ (tpy)
Assembly #1	92.4	5.26
Assembly #2	61.3	8.76
Body Operations	422.6	36.1
Paint #1	1865	59.1
Paint #2	1571	60.62
Plastics	1794	70.8
Powertrain	182.4	16.1

TABLE 4 – VOC and PM/PM₁₀ BACT Limits per Shop.

EMISSION AND OPERATING CAPS DESCRIPTION (CONTINUED):

D01 - Utility Boilers (545 MMBTU/HR)			
Allowable Emission Rates (lb/MMBTU Heat Input)			
Pollutant	Natural Gas ¹	# 2 Oil ²	
PM	7.45 x 10 ⁻³	1.43 x 10 ⁻²	
SO ₂	5.88 x 10 ⁻⁴	3.04 x 10 ⁻¹	
NO _X	4.90 x 10 ⁻²	1.43 x 10 ⁻¹	
CO	8.24 x 10 ⁻²	3.57 x 10 ⁻²	
VOC ³	5.39 x 10 ⁻³	1.80 x 10 ⁻³	
Reference Permit # C-86-117 (Revision 2)			
¹ Limts are based on July 1998 ed. of AP-42			
² Limits are based on September 1998 ed. of AP-42			
³ #2 Oil limit is based AP-42 TOC Emission Factor for distillate oil fired industrial boilers			

TABLE 5 – BACT Limits for Utility Boilers (Facilities Control).

D03 - Indirect Heat Exchangers > 1 MMBTU/HR			
Line 2 (69	Line 2 (690 MMBTU/HR)		
Allowable	Allowable Emission Rates (Tons/Year)		
Pollutant	Natural Gas		
PM	13.1		
SO ₂	1.0		
NO _X	172.3		
СО	144.7		
VOC	9.5		
Reference Permit # F-99-029			

TABLE 6 – BACT Limits for Line 2 Combustion Sources.

OPERATIONAL FLEXIBILITY: N/A